KYD-N019 Pillow Type Packaging Machine

1.Description:

Dual frequency conversion control, bag length can be set and cut in one step, saving time and film, interface, features easy and quick setting and operation, self failure diagonsis, clear failure display. High sensitivity photoelectric eye color tracing, numerical input of cutting sealing position for extra accuracy. Temperature independent PID control, more suitable for packaging different materials. Positioned stop function, without sticking knife or wasting film. Simple driving system, reliable working, convenient maintenance. All control is realized through software, easy for function adjusting and technical upgrade.

2. reennear paramete			
Machine size:	3770*720*1450mm	Pressure:	6kg/c m ²
Yield:	40-230pcs/min	Fuselage material:	
			Aluminium alloy
Machine weight:	900KG	Control mode:	PLC
Voltage:	220V	Detection mode:	Photoelectric detection
Power:	2.6KW	Remark:	Inflatable device

2. Technical parameter:

3.Feature

1. Multifunction and Higher Efficiency, lower trouble.

2. Stainless steel structure, independent electrical control box.

3. The parts surface adopts chorme dealing, covering parts of stainless steel, looking beautiful and clean.

4. Machine with Multifunction, and change the model for each different size shoes cover producing.

5. Automatic piece Account, Machine with Stop Protection.